

König Brush Pen Covering Lacquer

288 000

Intended Use

- For touch-up prior to filling scratches and holes with König fillers.
- For the covering touch-up by brush on wood, plastic and metal surfaces.
- To obtain basic shades and to replicate the grain pattern.
- For the colouring of Rex-Lith Wood and Transparent.
- For indoor and outdoor use.

Characteristics

- Pigmented acrylic-based covering lacquer.
- Dries rapidly.
- High opacity.
- Overcoatable with all König touch-up and aerosol lacquers.
- Good adhesion to many lacquer, plastic and metal surfaces (not to Soft-PVC).
- Good lightfastness and weather-resistance (adequate coat thickness required!).
- Limited PVC-resistance (window/door gaskets).
- Dried up lacquer on the mixing palette can be dissolved and well intermixed (also with Brush Pen Clear Lacquer).

Application Notes

Shake pen well before use – approx. 20 seconds. Rattle of mixing balls must be heard. Take off cap. Hold pen with tip pointing upwards and de-aerate pen while squeezing area marked 'P' (audible pressure compensation). Now, hold pen with tip pointing downwards over a small wooden board, chip, tissue or cotton cloth and slowly press area marked 'P' until colour drips onto the base. Stir colour lacquer drop on the base with the brush tip to achieve an optimum spreading of the liquid medium in the brush tip. Do not touch up too wet – especially when applying fine lines. When brush tip has dried up, either re-pump lacquer or dampen brush tip with Cellulose Thinner. Replace cap after use. Surfaces to be treated must be free of dust, grease and silicone.

Recommendation: If pen is not used for a long period of time, clean brush tip with Cellulose Thinner.

Physical Properties and Shelf Life

Dust-dry:	after approx. 1-2 minutes
Touch-proof:	after approx. 2-5 minutes (dependent on room temperature and coat thickness)
Lightfastness:	good
Weather resistance:	good
Shelf life:	minimum 2 years (stored at room temperature, in unopened original container)

Safety Precautions

Please refer to label and material safety data sheet.

Disposal

- Do not allow product to enter drains or watercourses.
- Non-contaminated packaging may be recycled.
- Leftover material to be disposed of according to the European Waste Code 080111 – *waste paint and varnish containing organic solvents or other dangerous substances*.
- For more detailed information, please refer to the Material Safety Data Sheet for this product or ask your local waste industry office.

Packaging

On request.

*Further information and Material Safety Data Sheet on the internet at
www.heinrich-koenig.de*

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for his or her particular purpose(s).



®
Seit 1892

Heinrich König; a V< & Co. KG

An der Rosenhelle 5 • D-61138 Niederdorfelden

Phone: 0 61 01-53 60 0 • Fax: 0 61 01-53 60 11

E-mail: info@heinrich-koenig.de

2021.43