

Intended Use

- To maintain the value of thick layer glazed wood windows (application recommended every six months).
- To renovate foiled UPVC windows after weathering.
- Provides a new sheen to window frames and extends renovation intervals.
- For indoor and outdoor use.

Characteristics

- Physically drying, waterborne lacquer.
- Very simple and uncomplicated to use.
- Dries rapidly.
- UV-protection, resistant to yellowing.
- Soil-resistant and water-repellent protective coating.
- Sheen level: silk gloss.

Application Notes

Shake container well before use. Surface to be treated must be dry and free of grease. If necessary, clean with Eco-Cleaner. Test Universal Maintenance Lacquer on an inconspicuous area first to ensure compatibility with the surface. Do not use Universal Maintenance Lacquer in direct sunlight or on surfaces that are heated up. Processing temperature 12-25°C.

Pour Universal Maintenance Lacquer into a flat bowl, soak Maintenance Sponge or sponge cloth and spread material extensively on the surface. Strip off sparsely, just once lengthwise, do not polish.

After a few minutes the treated area will be dry and after approx. 30 minutes hard-wearing. Wash out Maintenance Sponge/sponge cloth with water after use.

Even UPVC windows (foiled), which have become dull and matt by environmental influences, can be refurbished with Universal Maintenance Lacquer again and again.

Physical Properties and Shelf Life

Character:	dispersion lacquer, aqueous
Dust-dry:	after approx. 5-10 minutes
Hard-wearing:	after approx. 30 minutes
Coverage:	approx. 2-4 m ² per 200 ml (single application)
Lightfastness:	good
Weather resistance:	good
Water resistance:	very good
Adhesion:	very good
Elasticity:	very good
Shelf life:	minimum 1 year (stored upright at room temperature, in unopened original container)

Protect from frost!

Safety Precautions

- The mixture is classified as not hazardous according to regulation (EC) No. 1272/2008 [CLP].

Disposal

- Dispose of containers with the normal household waste only when completely empty or dried out.
- Leftover material to be disposed of in accordance with EWC 080112 (waste paint and varnish other than those mentioned in 080111).

Packaging

On request.

*Further information and Material Safety Data Sheet on the internet at
www.heinrich-koenig.de*

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for his or her particular purpose(s).



®
Seit 1892

Heinrich König ; a V<`& Co. KG

An der Rosenhelle 5 • D-61138 Niederdorfelden

Phone: 0 61 01-53 60 0 • Fax: 0 61 01-53 60 11

E-mail: info@heinrich-koenig.de

2021.43